

Generators

Generator and Lighting Towers - Model 3200iSK

[Brochure](#)



[Specification Chart](#)

For party hire, building and construction, shires, councils - anywhere portable lighting is required!

CROMMELINS LIGHTING TOWER attaches easily to the 3200iS and 4300iS SUBARU Silent Inverter generators. These generators provide excellent power for the tower due to their low noise output and superior inverter technology.

The Inverter control system achieves high quality output with less fluctuation and wave distortion and allows the engine speed to be automatically adjusted in direct proportion to the load applied maximising fuel efficiency, while Many portable lighting towers can have fluctuating light intensity due to unstable power generation, which can result in inconsistent lighting and shadowing.

Specifications & Features:

- 360° rotation of mast
- Height: 4.6 m
- Output: 4 x 500 watt halogen globes
- Manually operated pneumatic pump

LIGHTING TOWERS ARE ALSO SOLD SEPARATELY AND ATTACH TO MOST GENERATORS!

Model 3200iSK

[300dpi professional image for advertising](#)



[view](#)



[view](#)

GENERATOR
AC Output
DC Output
Power Factor
Over Current Protector

Model 3200iSK

Specifications
 2800 watts
 12 - 8.3
 1.0
 Electronic circuit breaker

Model 4300iSK

Specifications
 3800 watts
 12 - 8.3
 1.0
 Electronic circuit breaker

Noise Level at Rated Output (dB-7m)	58	62
ENGINE	Specifications	Specifications
Type	Air-cooled, 4-stroke, OHC Gasoline Engine	Air-cooled, 4-stroke, OHC Gasoline Engine
Model	SUBARU EX21 7.0HP	SUBARU EX27 9.0 HP
Displacement	212 mL	265 mL
Fuel	Automotive Unleaded Gasoline	Automotive Unleaded Gasoline
Fuel Tank Capacity	14.0 litres	16.0 litres
Continuous Operating Hours at Rated Output	8.4	6.6
Starting System	Electric and Recoil starter	Electric and Recoil starter
Dimensions LxWxH	537x482x583 mm	580x527x618 mm
Weight	59 kg	74 kg