

Generators

Imported SUBARU RGD Diesel Generators - Model RGD3310S Electric Start

[Brochure](#)



Model RGD3310S Electric Start

[300dpi professional image for advertising](#)

[Specification Chart](#)

SUBARU diesel generators are built for the toughest applications and feature both recoil and electric start operation, to suit all requirements. The RGD series are competitively priced generators packed with benefits:

- Easy starting provided by an electric starter with back up light-pull recoil starter and automatic decompression system
- Extra large fuel tank
- Brushless alternator eliminates the need for brush maintenance
- Compact and easy to handle
- Oil sensor automatically shuts off the engine when oil level drops too low
- Condensor voltage regulation ensures stable voltage output under all working conditions
- Economical performance guaranteed from the direct micro pump fuel injection system
- Quiet operation from the intake-exhaust system, direct injection combustion system, large capacity muffler and an efficient low noise double element air cleaner
- Operator friendly with front mounted control panel for easy access and resettable circuit breakers to protect from overloading or faulty appliances
- Long life durability is ensured by:
 - forced oil lubrication and totally balanced engine design
 - brushless alternator with trouble free condenser voltage regulation
 - full rubber shock mounts in a heavy duty steel roll frame



[view](#)



[view](#)

Model
Type

Voltage Regulator
Frequency

Rated Voltage
Rated output

Model RGD3310S Electric Start

RGD3310S
brushless, self exciting, 2 poles, single phase
Condensator type
50Hz
240
2700w

Model RGD5000S

RGD5000S
brushless, self-exciting, 2 poles, single phase
Condensator type
50Hz
240v
4800w

Maximum output	3000w	5500w
DC output	12V-8.3A (100w)	12V - 8.3A
Power factor	1.0	1.0
Engine	SUBARU DY27-2D air cooled 4 stroke diesel	SUBARU DY41D air cooled 4 stroke diesel
Fuel tank	7.8 L	16 L
Displacement	265cm ³	412cm ³
Operating hours at rated output	6.6	9.4
Dimensions	636x400x458mm	691x542x541
Dry weight	58.5 kg	110 kg