




125R

Lightweight brushcutter, perfect for homeowners. Easy starting with Smart Start recoil system, fuel pump and an always-ON auto return stop switch for trouble free starting. Equipped with double harness, easy loading semi-automatic trimmer head and grass blade. E-TECH engine for reduced emissions.



Combi-guard

The cutting attachment combi-guard can be used with either a grass blade or a trimmer head.



E-TECH engine

The E-TECH engine combines reduced exhaust emissions with a superior power/weight ratio.

125R

Engine specification

Cylinder displacement	28.0 cm ³
Power	0.8 kW / 1.1 hp
Cylinder bore	35 mm
Cylinder stroke	29 mm
Maximum power speed	8000 rpm
Maximum recommended engine speed	10000 rpm
Type of carburettor	Zama
Gear ratio/drive gear angle	1:1.40 / 30°
Fuel tank volume	0.4l
Fuel consumption	507 g/kWh
Shaft length	1446 mm
Shaft diameter	25.4 mm

Emission, vibration & noise data

Vibration idling left/right min	1.9 / 1.4 m/s ²
Vibration idling left/right max	1.9 / 1.4 m/s ²
Vibration top speed left/right min	3.9 / 3.2 m/s ²
Vibration top speed left/right max	5.4 / 4.1 m/s ²
Sound level, min/max	94 dB(A) / 98 dB(A)
Noise emission, L _{WA}	108 dB(A)
Emission, HC	91.6 g/kWh
Emission, NOx	1.1 g/kWh

Emission, CO 236 g/kWh

Overall dimensions

Weight 5.0 kg

Logistics